

# MALLARD POINT

## GAS INSERTS

**COUNTRY STOVES**  
A LIFETIME OF WARMTH



**Mallard Point 34**



**Mallard Point 32**

### STANDARD FEATURES

- Available in 34", 32", and 27" models to fit most common fireplace sizes.
- Electronic ignition models include a battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen\*.
- Beautifully crafted high-definition ceramic fiber log set.
- State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- Choose between several distinctive styles of accessory façades to match the look of your existing décor (required)
- Factory installed blower with six speed settings to fine tune your heating needs.
- Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- 20 year limited warranty.

\*All applicable models comply with ANSI Z21.50/88 barrier requirements.

### OPTIONS

#### FACADES



Vista Façade



Full View Façade

#### ACCENT TRIMS



Vista - Vista Trim



Full View - Frontier



Full View - Highliner



Full View - Iron Rail

#### REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.

#### LINERS



Black Tie



Porcelain



Heritage Brown



Flat Black

SPECIFICATIONS

PRODUCT DIMENSIONS

|                                      |           | Mallard Point 27 | Mallard Point 32 | Mallard Point 34 |
|--------------------------------------|-----------|------------------|------------------|------------------|
| Width                                | Front     | 26-5/8"          | 31-5/8"          | 33-5/8"          |
|                                      | Back/Rear | 16-3/4"          | 21"              | 23"              |
| Height                               | Overall   | 17-7/8"          | 19-3/8"          | 23-7/8"          |
| Depth                                | Overall   | 14-7/8"          | 15-7/8"          | 16-1/4"          |
| To Centerline (CL) of 3" Flue Collar |           | 8-3/16"          | 9-3/4"           | 10"              |

CLEARANCES

MINIMUM CLEARANCES TO COMBUSTIBLES

|   |                                                              | Mallard Point 27 | Mallard Point 32 | Mallard Point 34 |
|---|--------------------------------------------------------------|------------------|------------------|------------------|
| A | 1-1/2" Top facing to bottom of appliance                     | 32"              | 32"              | 36"              |
| B | Side facing or side wall to center of glass                  | 23"              | 25-7/8"          | 26-7/8"          |
| C | 6" Mantel to bottom of appliance                             | 34"              | 32"              | 36"              |
| D | Vertical distance from base of appliance to hearth extension | 0" 4"            | 0" 10"           | 0" 10"           |
| E | Minimum horizontal distance from front of appliance          | 10" 0"           | 2" 0"            | 2" 0"            |

Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.


SURROUND SIZING

|                              | Mallard Point 27 | Mallard Point 32 | Mallard Point 34 |
|------------------------------|------------------|------------------|------------------|
| Standard Surround 3-pc       | 26" H X 37" W    | 26" H X 41" W    | 31" H X 41" W    |
|                              | 26" H X 41" W    | 26" H X 46" W    | 31" H X 46" W    |
|                              | 30" H X 37" W    | 33" H X 41" W    | 34" H X 41" W    |
|                              | 30" H X 41" W    | 33" H X 46" W    | 34" H X 46" W    |
| Standard Surround 1-pc       | N/A              | N/A              | N/A              |
| 4 Sided - Able to be Trimmed | 38" H X 46" W    | 38" H X 46" W    | 42" H X 46" W    |
| Cast Surround                | N/A              | N/A              | N/A              |

FIREPLACE SIZING

|             | Mallard Point 27 | Mallard Point 32 | Mallard Point 34 |
|-------------|------------------|------------------|------------------|
| Front Width | 27"              | 32"              | 34"              |
| Height      | 18"              | 19-1/2"          | 24"              |
| Rear Width  | 17"              | 22"              | 24"              |
| Depth       | 15"              | 16"              | 16"              |

DIAGRAMS



MALLARD POINT 27

**BTU INPUT NG:** 18,000 - 25,000  
**BTU INPUT LP:** 16,000 - 22,500  
**HEATING CAPACITY:** 450 - 1,625 square feet  
**AFUE EFFICIENCY:** 78% (NG) 75% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 73% (NG) 73% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

MALLARD POINT 32

**BTU INPUT NG:** 23,000 - 34,000  
**BTU INPUT LP:** 28,000 - 34,000  
**HEATING CAPACITY:** 500 - 1,750 square feet  
**AFUE EFFICIENCY:** 71% (NG) 74% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 65% (NG) 70% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

MALLARD POINT 34

**BTU INPUT NG:** 25,000 - 38,000  
**BTU INPUT LP:** 27,000 - 35,500  
**HEATING CAPACITY:** 500 - 2000 square feet  
**AFUE EFFICIENCY:** 67% (NG) 73% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 66% (NG) 68% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard