

MALLARD POINT

GAS INSERTS

COUNTRY STOVES
A LIFETIME OF WARMTH



Mallard Point 34



Mallard Point 32

STANDARD FEATURES

- Available in 34", 32", and 27" models to fit most common fireplace sizes.
- Electronic ignition models include a battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen*.
- Beautifully crafted high-definition ceramic fiber log set.
- State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- Choose between several distinctive styles of accessory façades to match the look of your existing décor (required)
- Factory installed blower with six speed settings to fine tune your heating needs.
- Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- 20 year limited warranty.

*All applicable models comply with ANSI Z21.50/88 barrier requirements.

OPTIONS

FACADES



Vista Façade



Full View Façade

ACCENT TRIMS



Vista - Vista Trim



Full View - Frontier



Full View - Highliner



Full View - Iron Rail

REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.


LINERS



Black Tie



Porcelain



Heritage Brown



Flat Black

SPECIFICATIONS

PRODUCT DIMENSIONS

		Mallard Point 27	Mallard Point 32	Mallard Point 34
Width	Front	26-5/8"	31-5/8"	33-5/8"
	Back/Rear	16-3/4"	21"	23"
Height	Overall	17-7/8"	19-3/8"	23-7/8"
Depth	Overall	14-7/8"	15-7/8"	16-1/4"
To Centerline (CL) of 3" Flue Collar		8-3/16"	9-3/4"	10"

CLEARANCES

MINIMUM CLEARANCES TO COMBUSTIBLES

		Mallard Point 27	Mallard Point 32	Mallard Point 34
A	1-1/2" Top facing to bottom of appliance	32"	32"	36"
B	Side facing or side wall to center of glass	23"	25-7/8"	26-7/8"
C	6" Mantel to bottom of appliance	34"	32"	36"
D	Vertical distance from base of appliance to hearth extension	0" 4"	0" 10"	0" 10"
E	Minimum horizontal distance from front of appliance	10" 0"	2" 0"	2" 0"

Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.


SURROUND SIZING

	Mallard Point 27	Mallard Point 32	Mallard Point 34
Standard Surround 3-pc	26" H X 37" W	26" H X 41" W	31" H X 41" W
	26" H X 41" W	26" H X 46" W	31" H X 46" W
	30" H X 37" W	33" H X 41" W	34" H X 41" W
	30" H X 41" W	33" H X 46" W	34" H X 46" W
Standard Surround 1-pc	N/A	N/A	N/A
4 Sided - Able to be Trimmed	38" H X 46" W	38" H X 46" W	42" H X 46" W
Cast Surround	N/A	N/A	N/A

FIREPLACE SIZING

	Mallard Point 27	Mallard Point 32	Mallard Point 34
Front Width	27"	32"	34"
Height	18"	19-1/2"	24"
Rear Width	17"	22"	24"
Depth	15"	16"	16"

DIAGRAMS



MALLARD POINT 27

BTU INPUT NG: 18,000 - 25,000
BTU INPUT LP: 16,000 - 22,500
HEATING CAPACITY: 450 - 1,625 square feet
AFUE EFFICIENCY: 78% (NG) 75% (LP)
ENERGUIDE (P4) EFFICIENCY: 73% (NG) 73% (LP)
BLOWER: 150-CFM
REMOTE CONTROL: Standard

MALLARD POINT 32

BTU INPUT NG: 23,000 - 34,000
BTU INPUT LP: 28,000 - 34,000
HEATING CAPACITY: 500 - 1,750 square feet
AFUE EFFICIENCY: 71% (NG) 74% (LP)
ENERGUIDE (P4) EFFICIENCY: 65% (NG) 70% (LP)
BLOWER: 150-CFM
REMOTE CONTROL: Standard

MALLARD POINT 34

BTU INPUT NG: 25,000 - 38,000
BTU INPUT LP: 27,000 - 35,500
HEATING CAPACITY: 500 - 2000 square feet
AFUE EFFICIENCY: 67% (NG) 73% (LP)
ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)
BLOWER: 150-CFM
REMOTE CONTROL: Standard