



Kozy-King

Wood and Coal Furnace



85.1%
EFFICIENCY



- A UL Listed wood and coal burning furnace.
- Fully automatic with secondary afterburner for maximum efficiency with less fuel.



MADE IN USA



Wood and Coal Furnace

These furnaces are designed to meet your heating needs. Our goal is to serve your needs with a very efficient, clean burning furnace that takes less fuel to heat your home.

Features:

- Burns coal and wood
- Cast iron shaker grates
- Cast Iron, airtight fire and ash door
- Large loading door
- Large ash pan
- 3-speed blower
- 3/16" plate steel
- Fully automatic
- Wall thermostat controlled
- Fan and limit safety controls
- Cast iron baffle
- Special tubes through fire box for maximum heat circulation
- Special tubes through fire box for maximum heat circulation
- Removable oxygen afterburner
- Forced draft
- Insulated cabinet
- 80/20 combustion bypass
- Filter box left or right intake (18" x 18")
- 85.1% Efficiency rating



Inside Fire Box.

Manufactured by DS Machine
Gordonville, Pennsylvania
(717) 769-2952

Specifications	#300-09	#400-09
Fire box size	16 x 22	16 x 29
Fire chamber volume	6.2 cu. ft.	8 cu. ft.
Weight	730 lbs	820 lbs
Width	28.5"	28.5"
Height	53"	53"
Depth	31"	43"
Depth including filter box	51"	58"
Flue size	6"	7"
Warranty firebox	5 years	5 years
Height to center of flu	47.5"	47.5"
Ash door size	6" x 16.5"	6" x 16.5"
Load door size	14" x 14"	14" x 14"
Heating sq. ft.	Up to 3,000 sq. ft.	Up to 4,000 sq. ft.
BTU rating	140,000	205,000
Blower capacity 3-speed	1650 - 1350 1100 cfm	1650 - 1350 1100 cfm
Plenum outlet size	18" x 18"	18" x 18"
Efficiency	85.1%	85.1%
Clearance from Combustibles		
Side and rear	18"	18"
Front	48"	48"
Top of plenum to ceiling	2"	2"
Flue to wall	18"	18"

All units require a class "A" all fuel chimney installation that must conform to local and state codes.

***Safety tested and labeled to U.L. Standards by Guardian Fire Testing, to UL 391, ETL78-1, CAN/CSA B-366.1**

DEALER :