




A classic design combined with high-efficiency heating performance to provide your home with relaxing, reliable warmth.

LENNOX
HEARTH PRODUCTS

MERIT™
SERIES



The diagram shows a cross-section of a fireplace. The opening is defined by a black frame. The overall width of the opening is 29-3/4". The overall height of the opening is 19". The inner width of the opening is 19". The inner height of the opening is 15-1/4". The area below the opening is labeled "Hearth Extension". The height of the hearth extension is labeled "Hearth Height".



HEARTH HEIGHT	3/8"	2"	3"	4"
HEARTH EXTENSION	20"	17"	17"	0"
HEARTH WIDTH (MIN.)	33-1/2"			

HEATING CAPACITY*	900 – 2,000 SQ. FT.
BTU INPUT	NATURAL GAS HIGH 39,000 / LOW 27,500
	LP GAS (PROPANE) HIGH 39,000 / LOW 22,600
CANADIAN ENERGIGUIDE RATING	
	NATURAL GAS 67.09%
	LP GAS (PROPANE) 69.02%
STEADY-STATE EFFICIENCY**	80% – 84%
VENT PIPE	4" GAS-RATED B-VENT OR LISTED SINGLEWALL GAS VENT CHIMNEY LINER
BLOWER	150-CFM VARIABLE-SPEED (STANDARD)
POWER OUTAGE OPERATION	YES***
ZERO-CLEARANCE (METAL) AND METAL MASONRY FIREPLACE APPROVED	YES



Tested & Listed By  Portland Oregon USA



Obadiah's • 406-300-1776