

de manincor

Manufactured by: DE MANINCOR SPA
Italy - 38121 Trento • Via di Spini, 15
WWW.DEMANINCOR.IT
LISTED - COOK STOVE - WOOD BURNING

Tested by: GUARDIAN FIRE TESTING LAB.
I.S.O. 17025 TESTING
I.S.O. GUIDE 65 CERTIFICATION
WWW.FIRETESTING.COM




TESTED TO: **UL-1482 ULC-S627**

MODEL / MODELE:

SERIAL N. / N. DE SÉRIE:

MINIMUM CLEARANCES TO COMBUSTIBLE MATERIALS / DEGAGEMENT MINIMAL AUX MATERIAUX COMBUSTIBLES
TOP FUEL / CARNEAU SUPERIEUR
WITH SINGLE WALL CHIMNEY CONNECTOR / RACCORD DE CHEMINEE A PAROI SIMPLE

CEILING / PLAFOND



FLOOR / PLANCHER

FUEL - TESTED FOR WOOD. DO NOT OBSTRUCT SPACE UNDER STOVE. SPECIAL METHODS ARE REQUIRED WHEN PASSING THROUGH A WALL OR CEILING. SEE INSTRUCTIONS AND BUILDING CODES. DO NOT CONNECT THIS UNIT TO A CHIMNEY FLUE SERVING ANOTHER STOVE. FOR SAFE OPERATION, INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. KEEP HEATER DOOR CLOSED WHILE IN OPERATION. REPLACE GLASS ONLY WITH CERAMIC GLASS.

PREVENT HOUSE FIRES - INSTALL AND USE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND BUILDING CODES.


FLOOR PROTECTION - STOVE MUST BE PLACED ON A 3/8 IN. (9.5 MM) MILLBOARD PAD OR EQUIVALENT EXTENDING 18 IN. (457MM) IN FRONT (16 IN. (406MM) IN THE U.S.) AND 8 IN. (203MM) TO THE SIDES AND REAR OF THE UNIT.

CHIMNEY TYPE - MINIMUM 6 IN. (152MM) DIAMETER (APPROVED FOR RESIDENTIAL USE)

CHIMNEY CONNECTOR - 6 IN. (152MM) DIAMETER MIN. 24 GAUGE STEEL

CONTACT YOUR LOCAL BUILDING OFFICIALS ABOUT RESTRICTIONS AND INSTALLATION INSPECTION. A MINIMUM CLEARANCE OF 18 INCHES (457MM) TO THE CHIMNEY CONNECTOR MAY BE REQUIRED.

SIDE WALL / MUR LATÉRAL



FROM HEATER / DU POELE IN (MM)

A. 1 (25)

B. 8 (202)

E. 49.0 (1245)

FROM CHIMNEY CONNECTOR

DU RACCORD DE CHEMINEE IN (MM)

C. 18.0 (570)

D. 18.0 (570)

COMBUSTIBLE - POUR USAGE AVEC BOIS. NE RIEN ENTREPOSER SOUS LE POELE. DES METHODES SPECIALES SONT REQUISES LORS DU PERÇAGE D'UN MUR OU PLAFOND. VERIFIER LES DIRECTIVES ET LES CODES DE CONSTRUCTION. NE PAS RACCORDER A LA CHEMINEE D'UN AUTRE POELE. POUR UTILISATION SECURITAIRE, SUIVRE ATTENTIVEMENT LES INSTRUCTIONS DU FABRICANT. MAINTENIR LES PORTES DU POELE FERMEES PENDANT LE FONCTIONNEMENT. REMPLACER LE VERRE SEULEMENT AVEC DE LA CERAMIQUE.

PREVENIR LES INCENDIES - INSTALLER ET UTILISER SELON LES INSTRUCTIONS DU FABRICANT ET CODES DU BATIMENT.

PROTEGE PLANCHERS - POELE DOIT ETRE 3/8 PO (9.5MM) INSTALLE SUR UNE PLAQUE INCOMBUSTIBLE S'ETENDANT SUR 18 PO (457MM) A L'AVANT (16 PO (406MM) E.U.) ET 8 PO (203MM) A L'ARRIERE ET SUR LES COTES.

TYPE DE CHEMINEE - DIAMETRE MINIMAL 6 PO (152MM) - APPROUVEE POUR USAGE RESIDENTIEL

RACCORD DE CHEMINEE - DIAMETRE 6 PO (152MM) EPAISSEUR CALIBRE 24 ACIER

CONTACTEZ VOTRE MUNICIPALITE SUR LES RESTRICTIONS ET INSPECTIONS DE L'INSTALLATION. UN DEGAGEMENT MINIMAL DE 18 PO (457MM) AU CONNECTEUR DE CHEMINEE PEUT ETRE NECESSAIRE.

CAUTION



**HOT WHILE IN OPERATION - DO NOT TOUCH
KEEP CHILDREN AND CLOTHING AWAY
CONTACT MY CAUSE SKIN BURNS
SEE NAME PLATE AND INSTRUCTIONS
KEEP FURNISHINGS AND OTHER
COMBUSTIBLE MATERIALS A CONSIDERABLE
DISTANCE AWAY FROM THE APPLIANCE**

ATTENTION

**CHAUD PENDANT LE FONCTIONNEMENT - NE PASTOUCHER.
TENIR ÉLOIGNÉS LES ENFANTS ET LES VETEMENTS - LE CONTACT
PEU CAUSER DES BRULURES.
CONSULTEZ LA PLAQUE D'IMMATRICULATION ET LES
INSTRUCTIONS.
TENIR LES FOURNITURES ET AUTRES MATIERES COMBUSTIBLES À
DISTANCE DE L'APPAREIL**